

EVINRUDE®MODEL **300** V6

SPECIFICATIONS



Model	a. E300DSL b. E300DPX c. E300DCX d. E300DPZ e. E300DCZ	f. DE300PXIS g. DE300CXIS h. DE300PZIS i. DE300CZIS
Shaft Length mm (in) / Color	a. 508 (20") White b. / c. / f. / g. 635 (25") White d. / e. / h. / i. 762 (30") White	
Weight kg (lbs)	a. 237 (522) b. / c. / f. / g. 240 (528) d. / e. / h. / i. 242 (534)	
Engine Type	Loop Charged V6 90° E-TEC Direct Injection	
Bore x Stroke mm (in)	98 x 76 (3.854 x 3.000)	
Displacement cc (cu in)	3441 (210)	
Ignition System	IDI Fast Rise Inductive Ignition Knock Sensor	
Starter	Electric	
Trim Method	FasTrak™ Power Trim and Tilt	
Propshaft kilowatts (HP)*	224 kw (300 HP) @ 5500 RPM	
Full Throttle Operating Range	5000-6000 RPM	
Digital Shift & Throttle	f. / g. / h. / i. Digital Evinrude Icon	
Gear Ratio	1.85:1	
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode	
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator	
Cooling	Pressure and Temperature Controlled Water Cooled	
Steering	Remote	
Limited Warranty	5-year extended limited warranty: Standard 3 + Additional 2***	
Emissions Compliance	EPA 2013/CARB 2 STAR/EU 2006	



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Limited to new Evinrude MY10 and newer engines sold for recreational use only; excluding 65 commercial and 90 commercial models. Special conditions apply. 5 years or 750 hours, whichever occurs first. Contact your authorised BRP dealer, visit brp.com or refer to our Evinrude brochure for full details.

©2014 Bombardier Recreational Products Inc. All rights reserved.

®™ Trademark of Bombardier Recreational Products Inc. or its affiliates.