

MODEL 90 H.O. SPECIFICATIONS



Model ⁽¹⁾	a. E90DHL b. E90HSL c. E90HSX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c. 635 (25") White
Weight kg (lbs)	a. / b. 177 (390) c. 184 (405)
Engine Type	Loop Charged V4 60° E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.601 x 2.588)
Displacement cc (cu in)	1727 (105.4)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	Factory Tuned for High Performance
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	a. / b. 2.0:1 c. 2.25:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	5-year extended limited warranty: Standard 3 + Additional 2***
Emissions Compliance	EPA 2013/CARB 3 STAR/ EU 2006

(1) Selected models authorized to operate on Lake Constance (BS0)

* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Limited to new Evinrude MY10 and newer engines sold for recreational use only; excluding 65 commercial and 90 commercial models. Special conditions apply. 5 years or 750 hours, whichever occurs first. Contact your authorised BRP dealer, visit brp.com or refer to our Evinrude brochure for full details.

©2014 Bombardier Recreational Products Inc. All rights reserved.

®™ Trademark of Bombardier Recreational Products Inc. or its affiliates.

