

EVINRUDE®



9.8 HP / 7.2 kW

SPECIFICATIONS

ENGINE TYPE	2-CYLINDER / 4-STROKE
BORE X STROKE MM (IN)	(55 X 44) 2.17 X 1.73
DISPLACEMENT CC (CU IN)	209 (12.8)
GEAR RATIO	2.08:1
FULL THROTTLE RPM RANGE	5,000-6,000 RPM
WEIGHT KG (LBS)*	37 (81.5)
STARTING	ELECTRIC OR MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	800 (27)
FUEL TANK L	12 SEPARATE FUEL TANK
PROPELLER SELECTION RANGE CM (IN)	16.51-24.13 (6.5-9.5)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 80W, 6A (STANDARD ON ELECTRIC START MODELS)
STEERING	REMOTE CONTROL OR TILLER HANDLE
TRIM METHOD	MANUAL OR POWER TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

* Weight based on lightest model.